

## Survey of the East Bdy. of T. 27 S., R. 2 E.

## CHAINS

From the standard cor. of Tps. 27 S., Rs. 2 and 3 E.,  
which is an iron post, 3 ins. in diam., protruding  
9 ins. above ground, firmly set, with brass cap marked

S C  
T27S  
R2E | R3E  
S36 | S31

1927

from which,

A fir, 36 ins. in diam., bears N.35\*E., 62 lks. dist.,  
marked T 27 S R 3 E S 31 S C B T

A fir, 36 ins. in diam., bears N.35\*W., 72 lks. dist.,  
marked T 27 S R 2 E S 36 S C B T

Thence,

North, bet. secs. 31 and 36.

Over mountainous land, through heavy green timber and  
dense undergrowth.

Descend 50 ft. over NE. slope.

0.85 Spring branch, 1 lk. wide, course N.75\*W.

Ascend 70 ft. over SW. slope.

3.50 Spur, slopes W.

Descend 190 ft. over NW. slope.

12.75 Branch of French Creek, 20 lks. wide, course SW.

Ascend 75 ft. over SW. slope.

16.70 Spur, slopes S.60\*E.

20.75 Creek, 3 lks. wide, course S.30\*E.

Ascend 90 ft. over broken SW. slope.

22.50 Dry draw, course SW.

24.00 Head of spur, slopes S.10\*E.

35.00 Spur, slopes S.45\*W.

36.80 Spring branch, 1 lk. wide, course S.30\*W.

Ascend 160 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked