

East Boundary of T. 27 S., R. 2 E.

CHAINS

an iron post, 3 ft. long, 1 in. diam., under moss,  
with brass cap at cross (X) marked

$\frac{1}{4}$   
 S12 | S7  
 1928

from which

A Fir, 36 ins. diam., bears S.63\*E., 88 lks.  
dist., marked  $\frac{1}{4}$  S 7 B T.

A Pine, 9 ins. diam., bears N.13\*W., 53 lks.  
dist., marked  $\frac{1}{4}$  S 12 B T.

- 40.20 Draw, course SW.  
Ascend 775 ft. over broken SE slope.
- 55.90 Bend in way trail, bears SW and NW.
- 56.85 Way trail, bears NE and SW.
- 59.75 Bend in way trail, bears SE and NE.
- 69.85 Top of ridge, bears E and W.  
Descend 310 ft. over broken N slope.
- 74.90 Spur, slopes NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in  
the ground, for cor. of Secs. 1, 6, 7 and 12, with  
brass cap marked

T27S  
 R2E | R3E  
 S 1 | S 6  
 S12 | S 7  
 1928

from which

A Fir, 9 ins. diam., bears N.11\*E., 33 lks.  
dist., marked T 27 S R-3 E S 6 B T.

A Fir, 12 ins. diam., bears S.63\*E., 54 lks.  
dist., marked T 27 S R 3 E S 7 B T.

A Fir, 36 ins. diam., bears S.63\*W., 89 lks.  
dist., marked T 27 S R 2 E S 12 B T.

A Fir, 10 ins. diam., bears N.46\*W., 16 lks.  
dist., marked T 27 S R 2 E S 1 B T.