

North Boundary of T. 27 S., R. 2 E.

CHAINS

From the cor. of Ts. 26 and 27 S., Rs. 2 and 3 E., as hereinbefore described.

Thence,

S.89*53'W., on a true line bet. secs. 1 and 36.

Over mountainous land, through heavy timber and dense undergrowth.

Descend 470 ft. over NW. slope.

9.70 Copeland Creek, 40 lks. wide, course NE.

Ascend 655 ft. over broken SE. slope.

24.75 Spring branch, 1 lk. wide, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ $\frac{S\ 36}{S\ 1}$
1929

from which,

A cedar, 14 ins. in diam., bears S.45*W., 68 lks. dist., marked $\frac{1}{4}$ S 1 B T

A yew, 9 ins. in diam., bears N.5*W., 90 lks. dist., marked $\frac{1}{4}$ S 36 B T

Ascend 330 ft. over broken SE. slope, changes to NE.

44.30 Spring branch, 1 lk. wide, course SE.

72.70 Spring branch, 1 lk. wide, course NE.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 1, 2, 35 and 36, with brass cap marked

T26SR2E
 $\frac{S35\ | \ S36}{S\ 2\ | \ S\ 1}$
T27S
1929

from which,

A cedar, 40 ins. in diam., bears N.36*E., 59 lks. dist., marked T 26 S R 2 E S 36 B T

A fir, 16 ins. in diam., bears S.53*E., 33 lks. dist., marked T 27 S R 2 E S 1 B T