

Subdivisions, T. 27 S., R. 2 E.

CHAINS

From the S tandard cor. of secs. 35 and 36 on the S.bdy. of the Tp., which is an iron post, 2 ins. in diam., protruding 9 ins. above ground, firmly set, with, brass cap marked.

S C
T27SR2E
S35|S36
1927

from which,

A fir, 18 ins. in diam., bears N.40 $\frac{1}{2}$ *E., 126 lks. dist., marked T 27 S R 2 E S 36 S C B T

A pine, 14 ins. in diam., bears N.80*W., 90 lks. dist., marked T 27 S R 2 E S 35 S C B T

Thence,

N.0*01'W., bet. secs. 35 and 36.

Over mountainous land, through heavy green timber and dense undergrowth.

Descend 50 ft. over NE. slope.

2.50 Creek, 4 lks. wide, course SE.

Ascend 595 ft. over rock bluffs on S. slope.

16.40 Top of spur, slopes SE.

Descend 110 ft. over NE. slope.

24.80 Creek, 3 lks. wide, course E.

Ascend 125 ft. over SE. slope.

33.40 Top of spur, slopes E.

Descend 40 ft. over NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$
S35|S36
1929

from which,

A pine, 22 ins. in diam., bears S.47*E., 62 lks. dist., marked $\frac{1}{4}$ S 36 B T