

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S., R 2 E.

CHAINS

65.50

Draw, course NW.

Ascend 230 ft. over broken S W. slope.

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 6 ins. in the ground, to bedrock, supported in a mound of stone, 5 ft. base, 2 ft. high, for cor. of secs. 23, 24, 25 and 26, with brass cap marked

T27SR2E	
S23	S24
S26	S25
1929	

from which,

A fir, 24 ins. in diam., bears N.18\*E., 91 lks.

dist., marked T 27 S R 2 E S 24 B T

A cedar, 10 ins. in diam., bears S.37 $\frac{1}{2}$ \*E., 56 lks.

dist. marked T 27 S R 2 E S 25 B T

A cedar, 10 ins. in diam., bears S.28\*W., 48 lks.

dist., marked T 27 S R 2 E S 26 B T

A fir, 16 ins. in diam., bears N.47\*W., 106 lks.

dist., marked T 27 S R 2 E S 23 B T

This cor. is set at the foot of a rock bluff, 14 ft.

high, facing W.

Land, mountainous.

Soil, loose, coarse, rocky loam, 3rd rate.

Timber, fir, cedar, pine and hemlock.

Undergrowth, vinemaple, rhododendron, chinquapin, and snow brush.

S89\*52'E., on a random line bet. secs. 24 and 25.

40.00

Set temp.  $\frac{1}{4}$  sec. cor.

80.08

Intersect the E bdy. of the Tp., 16 lks. N. of the cor. of secs. 19, 24, 25 and 30, hereinbefore described.

Thence

N.89\*45'W., on a true line bet. secs. 24 and 25.

Over mountainous land, through heavy green timber and dense undergrowth.