

Subdivisions of T. 27 S., R. 2 E.

CHAINS


Ascend 255 ft. over NE. slope.

36.70 Twin Lakes Way Trail bears E. and W.

37.10 Top of spur, slopes SE.

Descend 50 ft. over S. slope.

41.64 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, supported by a mound of stone, 3 ft. base, 2 ft. high, for $\frac{1}{4}$ sec. cor., with brass cap marked



from which,

A fir, 12 ins. diam., bears S.87*E., 72 lks., dist., marked $\frac{1}{4}$ S 1 B T.

A fir, 10 ins. diam., bears S.32*W., 126 lks., dist., marked $\frac{1}{4}$ S 2 B T.

Descend 620 ft. over broken SE. slope.

61.00 Draw, course SE.

62.70 Draw, course SE.

Ascend 15 ft. over NE. slope.

67.50 Spur, slopes SE.

Descend 20 ft. over Se. slope.

70.30 Draw, course SE.

Ascend 15 ft. over NE. slope

72.40 Small spur, slopes SE.,

Descend 185 ft. over SE. slope.

78.70 Creek, 10 lks. wide, course E.

Ascend 60 ft. over N. slope.

80.06 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for witness cor. to cor. of secs. 1, 2, 11, and 12, with brass cap marked