


County Surveyor's Record, Douglas County, Oregon

9979
37

Subdivisions, T. 27 S., R. 2 E.

- CHAINS
7.10 Draw, course SE.
- 26.05 Top of divide, bet. the N. and S. Umpqua Rivers, bears E. and W.
- 26.15 Wooden post, 36x5x5 ins., set in a mound of stone, 4 ft. base, 2 ft. high, bears W., 85 lks. dist.
- 26.55 Stock driveway, bears SE. and NW.
Descend 275 ft. over NE. slope.
- 39.30 Intersect prospect shaft, 4 ft. square and 4 ft. deep.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked




from which,

A fir, 30 ins. in diam., bears N.85*E., 21 lks. dist., marked $\frac{1}{4}$ S 35 B T

A fir, 22 ins. in diam., bears N.22*W., 19 lks. dist., marked $\frac{1}{4}$ S 34 B T

Descend 870 ft. over broken NE. slope.

- 41.15 Emile trail, bears SE. and NW.
- 76.30 Draw, course NE.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 26, 27, 34 and 35, with brass cap marked



from which,

A hemlock, 12 ins. in diam., bears N.12*E., 62 lks. dist., marked T 27 S R 2 E S 26 B T

A hemlock, 12 ins. in diam., bears S.55*E., 27 lks. dist., marked T 27 S R 2 E S 35 B T

A pine, 20 ins. in diam., bears S.36*W., 84 lks. dist., marked T 27 S R 2 E S 34 B T