

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S., R. 2 E.

<p>CHAINS 29.50 33.10 40.00 43.00 44.50 60.10 69.80 80.00</p>	<p>Ascend 135 ft. over S. slope.</p> <p>Ascend 175 ft. over SE. slope.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked</p> <div style="text-align: center;"> $\frac{1}{4}$ S15 S14 1929 </div> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor., as no bearing trees were available.</p> <p>Ascend 45 ft. over SE. slope</p> <p>Ridge, bears E. and W.</p> <p>Descend 470 ft. over NE. slope.</p> <p>Twin Lakes Way Trail, by upper junction, bears E. and W.</p> <p>Spur, slopes NE.</p> <p>Descend 280 ft. over NW. slope.</p> <p>Spring branch, 1 lk. wide, course NE.</p> <p>Descend 70 ft. over N. slope.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in ground to bed rock, supported by mound of stone, $2\frac{1}{2}$ ft. base, 14 ins. high, for cor. of secs. 10, 11, 14, and 15, with brass cap marked</p> <div style="text-align: center;"> T27SR2E S10 S11 S15 S14 1929 </div> <p>from which,</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.4*E., 125 lks., dist., marked T 27 S R 2 E S 11 B T.</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears S.55*E., 26 lks., dist., marked T 27 S R 2 E S 14 B T.</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears S.43*W., 25 lks., dist., marked T 27 S R 2 E S 15 B T.</p> <p style="padding-left: 40px;">A pine, 54 ins. diam., bears N.12*W., 191 lks., dist., marked T 27 S R 2 E S 10 B T.</p> <p>Land; mountainous</p> <p>Soil; loose, coarse, rocky loam, 3rd rate.</p> <p>Timber; fir, pine, hemlock, cedar, and yew.</p>
--	---