

County Surveyor's Record, Douglas County, Oregon

48

Subdivisions of T. 27 S., R. 2 E.

CHAINS

the ground, for cor. of secs. 2, 3, 10, and 11, with brass cap marked

T27SR2E	
S 3	S 2
S 10	S 11
1929	

from which,

A fir, 30 ins. diam., bears N.56*E., 18 lks., dist., marked T 27 S R 2 E S 2 B T.

A fir, 32 ins. diam., bears S.54*E., 73 lks., dist., marked T 27 S R 2 E S 11 B T.

A fir, 12 ins diam., bears S.26*W., 67 lks., dist., marked T 27 S R 2 E S 10 B T.

A fir, 30 ins. diam.; bears N.78*W., 18 lks., dist., marked T 27 S R 2 E S 3 B T.

Land; mountainous.

Soil; loose, coarse, rocky loam, 3rd rate.

Timber; fir, hemlock, cedar, and pine.

Undergrowth; vinemaple, rhododendron, and chinquapin.

- 40.00 S.89*42'E., on a random line bet. secs. 2 and 11. Set temp. $\frac{1}{4}$ sec. cor.
- 80.04 Intersect N. and S. line, 17 lks. S. of the true point for cor. of secs. 1, 2, 11, and 12. Thence, From true point for cor. of secs. 1, 2, 11, and 12 N.89*49'W., on true line bet. secs. 2 and 11 Over mountainous land, through heavy timber and dense undergrowth. Ascend 40 ft. over broken NE. slope.
- 4.70 Creek, 10 lks. wide, course NE. Ascend 400 ft. over broken SE. slope.
- 14.90 Draw, course SE.
- 19.45 E. edge of meadow, bears N. and S.