

Subdivisions, T. 27 S., R. 2 E.

CHAINS	Ascend 160 ft. over broken SE. slope.
34.30	Spring branch, 1 lk. wide, course SE.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\begin{array}{c} \frac{1}{4} \\   \\ \text{S28}   \text{S27} \\   \\ 1929 \end{array}$
	from which,
	A fir, 5 ins. in diam., bears N.63*E., 59 lks. dist., marked $\frac{1}{4}$ S 27 B T
	A fir, 48 ins. in diam., bears N.47*W., 28 lks. dist., marked $\frac{1}{4}$ S 28 B T
	Ascend 140 ft. over SE. slope.
43.90	Spur, slopes E.
	Descend 90 ft. over NE. slope.
49.70	Spring branch, 1 lk. wide, course NE.
	Ascend 400 ft. over SE. slope.
68.25	Copeland Creek Way Trail, bears NE. and SW. on top of spur, sloping NE.
	Descend 475 ft. over N. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap marked
	$\begin{array}{c} \text{T27SR2E} \\ \text{S21}   \text{S22} \\ \text{S28}   \text{S27} \\   \\ 1929 \end{array}$
	from which,
	A hemlock, 8 ins. in diam., bears N.66*E., 61 lks. dist., marked T 27 S R 2 E S 22 B T
	A hemlock, 12 ins. in diam., bears S.43*E., 44 lks. Dist., marked T 27 S R 2 E S 27 B T
	A hemlock, 6 ins. in diam., bears S.36 $\frac{1}{2}$ *W., 24 lks. dist., marked T 27 S R 2 E S 28 B T