

Subdivisions, T. 27 S., R. 2 E.

CHAINS	
	N.0*02'W., bet. secs. 9 and 10.
	Over mountainous land, through heavy green timber and dense undergrowth.
	Descend 415 ft. over NE. slope.
22.90	Creek, 1 lk. wide, course E.
	Ascend 85 ft. along broken E. slope.
31.80	Moist draw, course E.
34.70	Spur, slopes E.
	Descend 65 ft. over NE. slope.
38.70	Draw, course SE.
	Ascend 35 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S 9 S 10 1929
	from which,
	A fir, 16 ins. in diam., bears S.48*E., 48 lks. dist., marked $\frac{1}{4}$ S 10 B T
	A fir, 20 ins. in diam., bears S.63*W., 43 lks. dist., marked $\frac{1}{4}$ S 9 B T
	Ascend 165 ft. over SE. slope.
48.50	Spur, slopes S.70*E.
	Descend 175 ft. over NE. slope.
57.65	Draw, course E.
	Ascend 25 ft. over SE. slope.
60.20	Spur, slopes N.75*E.
	Descend 25 ft. over NE. slope.
62.70	Draw, course S.75*E.
	Ascend 315 ft. over SE. slope.
77.30	Spur, slopes E.
	Descend 20 ft. over NE. slope.
80.00	Set a basalt stone, 24x18x14 ins., 18 ins. in the ground for cor. of secs. 3, 4, 9 and 10, marked with a cross (X) on top, 3 notches on E., and 5 notches on S. edges.