

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S., R. 2 E.

CHAINS

A fir, 10 ins. in diam., bears S.73*E., 22 lks. dist., marked 1/2 S 3 B T

A fir, 12 ins. in diam., bears N.65*W., 28 lks. dist., marked 1/2 S 4 B T

40.00 Spur, slopes NE.

44.85 E. edge of rock bluff, 75 ft. high, bears NW. and SW.

45.75 Twin Lakes Way Trail, bears NE. and SW.

Descend 160 ft. over SE. slope.

52.50 Draw, course E.

Ascend 445 ft. over NE. slope.

80.70 The cor. of secs. 3, 4, 9 and 10.

Land, mountainous.

Soil, loose coarse, rocky loam, 3rd rate.

Timber, fir, hemlock and cedar.

Undergrowth, vinemaple and rhododendron.

From the standard cor. of secs. 32 and 33, which is an iron post, 2 ins. in diam., protruding 9 ins. above ground, firmly set, with brass cap marked.

S	C
T27S	R2E
S32	S33
1927	

from which,

A cedar, 38 ins. in diam., bears N.32*E., 73 lks. dist., marked T 27 S R 2 E S 33 S C B T

A fir, 30 ins. in diam., bears N.32*W., 49 lks. dist., marked T 27 S R 2 E S 32 S C B T

Thence,

N.0*03'W., bet. secs. 32 and 33.

Over mountainous land, through heavy green timber and dense undergrowth.

Along rolling bench, slopes SE.

13.75 Leave bench, bears E. and W.

Ascend 255 ft. over broken SE. slope.