

Subdivisions, T. 27 S., R. 2 E.

CHAINS

S 28 on E., and

$\frac{1}{4}$ S 29 on W. side

from which,

A fir, 24 ins. in diam., bears N.14*E., 48 lks.

dist., marked $\frac{1}{4}$ S 28 B T

A fir, 14 ins. in diam., bears S.66*W., 27 lks.

dist., marked $\frac{1}{4}$ S 29 B T

Descend 60 ft. over NE. slope.

43.20 Same creek, 3 lks. wide, course NW.

Descend 70 ft. over NW. slope.

52.20 Bottom of descent.

Ascend 40 ft. over SW. slope.

58.40 Small spur, slopes NW.

Descend 190 ft. over N. slope.

66.40 Creek, 2 lks. wide, course NW.

67.30 Copeland Creek, 13 lks. wide, course NE.

Ascend 300 ft. over SE. slope.

71.70 Spring branch, 1 lk. wide, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for cor. of secs. 20, 21, 28 and 29, with brass cap marked

T27SR2E
S20|S21
S29|S28
1929

from which,

A fir, 12 ins. in diam., bears N.66*E., 50 lks.

dist., marked T 27 S R 2 E S 21 B T

A chinquapin, 12 ins. in diam., bears S.60*E., 20 lks.

dist., marked T 27 S R 2 E S 28 B T

A pine, 16 ins. in diam., bears S.55*W., 75 lks.

dist., marked T 27 S R 2 E S 29 B T

A fir, 12 ins. in diam., bears N.43 $\frac{1}{2}$ *W., 74 lks.

dist., marked T 27 S R 2 E S 20 B T