

Subdivisions, T. 27 S., R. 2 E.

CHAINS	
	<p>A fir, 14 ins. in diam., bears N.39½*W., 40 lks. dist., marked ¼ S 30 B T</p> <p>Ascend 320 ft. over SW. slope.</p>
52.30	<p>Divide, bet. N. and S. Umpqua Rivers, bears SE. and NW.</p> <p>Descend 320 ft. over NE. slope.</p>
66.10	<p>Head of ravine, course N.</p> <p>Ascend 35 ft. over NW. slope.</p>
75.30	<p>Point of spur, slopes N.</p> <p>Descend 150 ft. over E. slope.</p>
79.76	<p>The cor. of secs 29, 30, 31 and 32.</p> <p>Land, mountainous.</p> <p>Soil, loose, coarse, rocky loam, 3rd rate.</p> <p>Timber, fir, cedar, hemlock and pine.</p> <p>Undergrowth, vinemaple, huckleberry, rhododendron, chinquapin, and second growth fir.</p>
	<p>N.0*04'W., bet. secs. 29 and 30.</p> <p>Over mountainous land, through heavy green timber and dense undergrowth:</p> <p>Ascend 35 ft. over SE. slope.</p>
1.95	<p>Small spur, slopes E.</p> <p>Descend 250 ft. over broken NE. slope.</p>
8.00	<p>Small spur, slopes NE.</p>
16.55	<p>Copeland Creek, 2 lks. wide, course NE.</p> <p>Ascend 130 ft. over SE. slope.</p>
25.90	<p>Spur, slopes E., from NW.</p> <p>Descend 205 ft. over NE. slope.</p>
40.00	<p>Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for ¼ sec. cor., with brass cap marked</p> <div style="text-align: center;"> <p>¼</p> <p> </p> <p>S30   S29</p> <p> </p> <p>1929</p> </div> <p>from which,</p> <p>A hemlock, 12 ins. in diam., bears S.28*E., 27 lks.</p>