

Subdivisions, T. 27 S., R. 2 E.

CHAINS

S.89\*47'W., on a random line bet. secs. 19 and 30.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.82 Intersect the W. bdy. of the Tp., 12 lks. S. of the cor. of secs. 19, 24, 25 and 30, which is an iron post, 2 ins. in diam., protruding 9 ins. above ground, firmly set, with brass cap marked

|      |     |
|------|-----|
| T27S |     |
| R1E  | R2E |
| S24  | S19 |
| S25  | S30 |
| 1927 |     |

from which,

A fir, 34 ins. in diam., bears N.35\*E., 59 lks. dist., marked T 27 S R 2 E S 19 B T

A fir, 14 ins. in diam., bears S.17\*E., 13 lks. dist., marked T 27 S R 2 E S 30 B T

A fir, 16 ins. in diam., bears S.70\*W., 22 lks. dist., marked T 27 S R 1 E S 25 B T

A fir, 34 ins. in diam., bears N.18\*W., 155 lks. dist., marked T 27 S R 1 E S 24 B T

Thence,

N.89\*52'E., on a true line bet. secs. 19 and 30.

Over mountainous land, through heavy timber and dense undergrowth.

Ascend 25 ft. over NW. slope.

2.85 Spur, slopes N.

Descend 50 ft. over NE. slope.

7.20 Spring branch, 1 lk. wide, course NE.

Ascend 225 ft. over NW. slope.

28.50 Spur, slopes NE.

Descend 20 ft. over SE. slope.

31.45 Ravine, course SE.

Ascend 120 ft. over W. slope.

39.82 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked