

Subdivisions, T. 27 S., R. 2 E.

CHAINS	
	N.89*57'E., on a random line bet. secs 17 and 20.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.16	Intersect the N. and S. line, 33 lks. N. of the cor. of secs. 16, 17, 20 and 21.
	Thence,
	N.89*49'W., on a true line bet. secs. 17 and 20.
	Over mountainous land, through heavy green timber and dense undergrowth.
	Ascend 420 ft. over broken SE. slope.
2.85	Draw, course SE.
12.95	Spur, slopes S.
	Descend 195 ft. over SW. slope.
30.00	Thence along broken S. slope.
40.08	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4} \frac{S17}{S20}$ 1929
	from which,
	A fir, 20 ins. in diam., bears S.41*W., 21 lks. dist., marked $\frac{1}{4}$ S 20 B T
	A fir, 24 ins. in diam., bears N.77*W., 46 lks. dist., marked $\frac{1}{4}$ S 17 B T
	Ascend 270 ft. over SE. slope.
51.95	Twin lakes Trail and telephone line, on top of ridge, bears N. and S.
	Descend 480 ft. over broken NW. slope.
60.45	Draw, course NW.
72.15	Creek, 1 lk. wide, course NE.
	Ascend 88 ft. over broken NE. slope.
75.25	Spring branch, 1 lk. wide, course NE.
80.16	The cor. of secs. 17, 18, 19 and 20.
	Land, mountainous.
	Soil, loose, coarse, rocky loam, 3rd rate.