


County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 27 S., R. 2 E.

CHAINS
40.23

Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for witness $\frac{1}{4}$ sec. cor., with brass cap marked



from which,

A fir, 36 ins. in diam., bears S.20*E., 31 lks. dist., marked W C $\frac{1}{4}$ S 17 B T

A fir, 20 ins. in diam., bears N.51*W., 85 lks. dist., marked W C $\frac{1}{4}$ S 18 B T

Ascend 180 ft. over SW. slope.

55.00 Spur, slopes W.

Descend 100 ft. over NW. slope.

58.10 Moist draw, course W.

Ascend 245 ft. over SW. slope.

69.50 Spur, slopes NW.

Descend 400 ft. over N. slope.

80.00 A basalt stone, 36x28x12 ins. above ground, for the cor. of secs. 7, 8, 17 and 18, I mark, with a cross (X) at the exact cor. point, 5 notches on the E., and 4 notches on the south edges.

from which,

A fir, 16 ins. in diam., bears N.18*E., 31 lks. dist., marked T 27 S R 2 E S 8 B T

A fir, 12 ins. in diam., bears S.69*E., 46 lks. dist., marked T 27 S R 2 E S 17 B T

A fir, 14 ins. in diam., bears S.53*W., 43 lks. dist., marked T 27 S R 2 E S 18 B T

A fir, 10 ins. in diam., bears N.20*W., 33 lks. dist., marked T 27 S R 2 E S 7 B T

Land, mountainous.

Soil, loose, coarse, rocky loam, 3rd rate.