

Subdivisions, T. 27 S., R. 2 E.

CHAINS

$\frac{1}{2}$
 S 7 | S 8
 W C
 1929

from which,

A fir, 26 ins. in diam., bears S.68*E., 168 lks.
dist., marked W C $\frac{1}{2}$ S 8 B T

A fir, 16 ins. in diam., bears S.64*W., 31 lks.
dist., marked W C $\frac{1}{2}$ S 7 B T

Ascend 260 ft. over SW. slope.

48.25 Top of cliff, 60 ft. high, bears E. and W., faces S.

48.65 Spur, slopes W.

Descend 145 ft. over NW. slope.

53.05 Dry creek bed, course NW.

Ascend 160 ft. over SW. slope.

63.55 Top of spur, slopes NW.

Descend 775 ft. over NW. slope.

74.05 Bend in draw, course, N.15*E., from SE.

79.57 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in
the ground, for the witness cor. of secs. 5, 6, 7 and
8, with brass cap marked

W C
 T27SR2E
 S 6 | S 5
 S 7 | S 8
 1929

from which,

A fir, 16 ins. in diam., bears N.83*E., 36 lks.
dist., marked W C T 27 S R 2 E S 8 B T

A fir, 18 ins. in diam., bears S.62*E., 68 lks.
dist., marked W C T 27 S R 2 E S 8 B T

A fir, 18 ins. in diam., bears S.61*W., 39 lks.
dist., marked W C T 27 S R 2 E S 7 B T

A fir, 26 ins. in diam., bears N.15*W., 31 lks.
dist., marked W C T 27 S R 2 E S 7 B T

80.00 Point for cor. falls on unsafe ground on the S. side of
Twin Lakes Creek, where it is impracticable to estab-
lish a permanent cor.