

Subdivisions of T. 27 S., R. 2 E.

CHAINS	
	S.0*06'W., on a true line bet. Secs. 5 and 6.
	Over mountainous land, through heavy green timber and dense undergrowth.
	Descend 625 ft. over broken S slope.
9.30	Top of bluff, 50 ft. high, bears SE and NW., faces SW.
23.60	Creek, 1 lk. wide, course NW.
	Ascend 790 ft. over series of rock bluffs on broken N slope.
40.13	Point for $\frac{1}{4}$ Sec. cor. falls on precipitous ground where it is impracticable to establish a permanent corner.
41.54	Set an iron post, 3 ft. long, 1 in. diam., 23 ins. in the ground to bedrock, supported in a mound of stone, for the witness $\frac{1}{4}$ Sec. cor., with brass cap marked
	from which
	A Fir, 8 ins. diam., bears N.68*E., 15 lks. dist., marked W C $\frac{1}{4}$ S 5 B T.
	A Pine, 9 ins. diam., bears N.77*W., 22 lks. dist., marked W C $\frac{1}{4}$ S 6 B T.
	This corner is set on a spur, slopes NW.
	Descend 995 ft. over broken SW slope.
60.65	Draw, course SW., thence descend over series of bluffs.
73.00	Draw, course SW.
79.90	Twin Lakes Creek, 4 lks. wide, course N.70*W.
80.13	The true point for cor. of Secs. 5, 6, 7 and 8.
	Land, mountainous.
	Soil, loose, coarse, rocky loam, 3rd rate.
	Timber, Fir, Hemlock, Cedar and Yew.
	Undergrowth, Rhododendron, Vinemaple, Chinquapin and Second growth timber.