

County Surveyor's Record, Douglas County, Oregon

10047

6th Standard Parallel South, T. 27 S., R. 3 E.
 As surveyed by Samuel C. Flint, U.S. Deputy Surveyor.
 Under Contract No. 473. Dated June 5, 1883.

CHAINS	East on S. boundary of Sec. 31 <div style="text-align: right;">Var. 18°E.</div>
2.70	Stream 25 lks. wide course N.80°W.
5.00	Ascend mountain.
40.00	Set post 45x4 ins. firmly in the ground for stand. $\frac{1}{4}$ sec. cor. marked S C on N. and S. faces, from which, A fir, 18 ins. in dia., bears S.25°W., 18 lks. dist., marked S C $\frac{1}{4}$ S B T A pine, 14 ins. in dia., bears S.25°E., 10 lks. dist., marked S C $\frac{1}{4}$ B T
75.75	Stream 4 lks. wide, course NW.
80.00	Set post 48x4 ins. firmly in the ground for stand. cor. to secs. 31 and 32 marked S C T 27 S R 3 E on N. S 32 on E. and S 31 on W. faces with 5 notches on E. and 1 on W. edges. from which, A pine, 18 ins. in dia., bears N.58°E., 61 lks. dist., marked T 27 S R 3 E S 32 B T A fir, 12 ins. in dia., bears N.20°W., 33 lks. dist., marked T 27 S R 3 E S 31 B T A fir, 36 ins. in dia., bears S.30°E., 25 lks. dist., marked S B T Land, 3rd rate. Mountainous and rocky. Timber, fir, hemlock, spruce and pine. Thick underbrush of vine maple, fir, cinnamon and mountain laurel.
	East on S. boundary of Sec. 32. Var. 18°45'E. Ascending ridge.
40.00	Set post 44x4 ins. firmly in the ground for stand. $\frac{1}{4}$ sec. cor. marked S C on N. and S. faces, from which, A fir, 18 ins. in dia., bears S.5°W., 20 lks. dist., marked S C $\frac{1}{4}$ S B T A fir, 18 ins. in dia., bears S.25°W., 23 lks. dist., marked S C $\frac{1}{4}$ S B T