

County Surveyor's Record, Douglas County, Oregon

East and North Boundaries and Subdivisions of T 27 S., R. 3 E.
 As surveyed by Herbert N. Raymond, W. S. C. E.
 Under special instruction, Dated Dec. 27, 1920

CHAINS	East Boundary.
	From the standard corner of Ts. 27 S., Rs. 3 and 4 E., which is an iron post, 3 ins. dia.; 8 ins. above ground, with brass cap marked and witnessed as described in the field notes of T. 28 S., R. 3 E.
	North bet. secs. 31 and 36.
	Desc. 75 ft. over NE. slope, through heavy timber and medium undergrowth.
16.80	Spring branch, 2 lks. wide, course NE., continue desc.
21.10	Creek, 6 lks. wide, course NE., asc. 160 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\begin{array}{c} \frac{1}{4} \\ \\ S\ 36\ \ S\ 31 \\ \\ 1929 \end{array}$
	from which,
	A fir, 12 ins. in dia., bears S.89*E., 41 lks. dist., marked $\frac{1}{4}$ S 31 B T
	A fir, 11 ins. in dia., bears N.54*W., 17 lks. dist., marked $\frac{1}{4}$ S 36 B T
	Spur, bears E. desc. 270 ft. over NE. slope.
51.70	Grave Creek, 8 lks. wide, course NE. asc. 190 ft. over SE. slope.
70.00	Spring branch, 4 lks. wide, course SE., continue ascend.
72.00	Spur, bears E., desc. 25 ft. over NE. slope.
77.50	Draw, drains E., asc. 10 ft. over SE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 25, 30, 31 and 36, with brass cap marked.
	$\begin{array}{c} T\ 27\ S \\ R\ 3\ E\ \ R\ 4\ E \\ \hline S\ 25\ \ S\ 30 \\ \hline S\ 36\ \ S\ 31 \\ 1929 \end{array}$
	from which,