

## County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

East Boundary.

## CHAINS

A fir, 34 ins. in dia., bears N.58\*E., 34 lks. dist.,  
marked T 27 S R 4 E S 6 B T

A fir, 14 ins. in dia., bears S.41\*E., 41 lks. dist.,  
marked T 27 S R 4 E S 7 B T

A fir, 16 ins. in dia., bears S.45\*W., 38 lks. dist.,  
marked T 27 S R 3 E S 12 B T

A fir, 26 ins. in dia., bears N.26\*W., 21 lks. dist.,  
marked T 27 S R 3 E S 1 B T

Land, rolling.

Soil, sandy and gravelly, 1st and 2nd rate.

Timber, fir, pine, and hemlock.

Undergrowth, hazel, buck brush, rhodendron, small  
fir, pine and hemlock.

North, bet. secs. 1 and 6.

Descend 65 ft. over rolling NE. slope, through heavy  
timber and dense undergrowth.

18.00 Brink of Clear Water canyon, bears NW. and SE. descend  
580 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in  
the ground, to bedrock, and build a mound of stone,  
4 ft. base, 1½ ft. high, around the post, for ¼ sec.  
cor., with brass cap marked.

$$\begin{array}{c} \frac{1}{4} \\ | \\ S 1 | S 6 \\ | \\ 1929 \end{array}$$

from which,

A fir, 18 ins. in dia., bears N.74\*E., 29 lks. dist.,  
marked ¼ S 6 B T

A fir, 20 ins. in dia., bears S.16\*W., 30 lks. dist.,  
marked ¼ S 1 B T

Descend 135 ft. over NE. slope.

51.10 Watson Creek, 8 lks. wide, course NW., ascend 40 ft.