

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

North Boundary.

CHAINS

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 34 ins. in the ground, for cor. of secs. 3, 4, 33 and 34, with brass cap marked.

T 26 S R 3 E
S 33 S 34
 S 4 S 3
 T 27 S
 1930

from which,

A fir, 10 ins. in dia., bears N.57*E., 9 lks. dist., marked T 26 S R 3 E S 34 B T

A fir, 6 ins. in dia., bears S.9*E., 46 lks. dist., marked T 27 S R 3 E S 3 B T

A fir, 12 ins. in dia., bears S.39*W., 31 lks. dist., marked T 27 S R 3 E S 4 B T

A fir, 10 ins. in dia., bears N.30*W., 19 lks. dist., marked T 26 S R 3 E S 33 B T

Land, mountainous.

Soil, gravelly and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock and cedar.

Undergrowth, vine maple, willow, mountain laurel, rhododendron, small fir, pine, hemlock and chinquapin.

East, on a true line, bet. secs. 3 and 34.

Ascend 80 ft. over W. slope, through medium timber and medium undergrowth.

12.50

Top of ascend, bears NW., and S. thence over rolling land,

14.80

Trail, bears NW. and SE.

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 32 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$\frac{1}{4}$ S 34
 S 3
 1930

from which,