

Township 27 South, Range 3 East.
Subdivision.

CHAINS

From the standard cor. of secs. 35 and 36, T, 27 S.,
R. 3 E., which is an iron post, 2 ins. in dia., 8 ins.
above ground, with brass cap marked and witnessed as
described in the field notes of T. 28 S., R. 3 E.
N.0°01'W., bet. secs. 35 and 36.

Ascend 10 ft. over SE. slope, through heavy timber and
medium undergrowth.

- 2.00 Spur, bears NE., descend 750 ft. over NE. slope.
- 8.63 Creek, 3 lks. wide, course NE.
- 10.18 Creek, 3 lks. wide, course NE.
- 27.55 Grave Creek, 6 lks. wide, course E., ascend 280 ft.
over SE. slope to

- 40.00 Set a country rock, 20x12x10 ins., 15 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. faces,
from which,
A fir, 20 ins. in dia., bears N.53°E., 38 lks. dist.,
marked $\frac{1}{4}$ S 36 B T
A fir, 18 ins. in dia., bears N.16°W., 9 lks. dist.,
marked $\frac{1}{4}$ S 35 B T

Ascend 430 ft. over broken SE. slope to

- 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 30 ins. in
the ground, for cor. of secs. 25, 26, 35 and 36,
with brass cap marked.

T 27 S R 3 E
S 26 S 25
S 35 S 36
1929

from which,

- A fir, 20 ins. in dia., bears N.45°E., 14 lks. dist.,
marked T 27 S R 3 E S 25 B T
- A fir, 16 ins. in dia., bears S.63°E., 33 lks. dist.,
marked T 27 S R 3 E S 36 B T
- A pine, 16 ins. in dia., bears S.42°W., 42 lks. dist.,
marked T 27 S R 3 E S 35 B T
- A pine, 20 ins. in dia., bears N.44°W., 15 lks. dist.,