

## County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.  
Subdivision.

CHAINS

A hemlock, 5 ins. in dia., bears S.73°E., 15 lks. dist.,  
marked T 27 S R 3 E S 25 B T

A hemlock, 8 ins. in dia., bears S.26°W., 18 lks. dist.,  
marked T 27 S R 3 E S 26 B T

A fir, 12 ins. in dia., bears N.27°W., 41 lks. dist.,  
marked T 27 S R 3 E S 23 B T

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd to 4th rate.

Timber, fir, pine, and hemlock.

Undergrowth, rhododendron, vine maple, huckleberry,  
small fir, pine and hemlock.

N.89°59'E., on random line, bet. secs. 24 and 25.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.90 Intersect E. bdy. 2 lks. N. of the cor. of secs. 19,  
24, 25 and 30.

Thence,

West, on a true line.

Ascend 415 ft. over E. slope, through heavy timber and  
light undergrowth.

15.00 Top of steep ascend. ascend 30 ft. over SE. slope.

28.00 Spur, bears NE., descend 265 ft. over W. slope to  $\frac{1}{4}$   
sec. cor., enter dense undergrowth.

39.95 Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in  
the ground, to bed rock, and build a mound of stone,  
3 ft. base, 1 ft. high, around the post, for  $\frac{1}{4}$  sec.  
cor., with brass cap marked.

$$\begin{array}{r} \frac{1}{4} \text{ S } 24 \\ \hline \text{S } 25 \\ 1929 \end{array}$$

from which,

A fir, 20 ins. in dia., bears N.52°E., 11 lks. dist.,  
marked  $\frac{1}{4}$  S 24 B T