

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS	
	S.0*13'E., on a true line. Over rolling land, through heavy timber and medium undergrowth.
25.45	A road, bears NW. and SE.
42.89	Set an iron post, 3 ft. long, 1 in. in dia., 32 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 2 \mid \text{S } 1 \\ 1929 \end{array}$
	from which, A fir, 30 ins. in dia., bears S.66*E., 37 lks. dist., marked $\frac{1}{4}$ S 1 B T A hemlock, 18 ins. in dia., bears S.78*W., 48 lks. dist., marked $\frac{1}{4}$ S 2 B T
82.89	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, sandy and gravelly, 1st, and 2nd rate. Timber, fir, pine, hemlock and yew. Undergrowth, hazel, huckleberry, small fir, pine, hemlock and yew.
	From the standard cor. of secs. 34 and 35, T.27S., R. 3 E., which is an iron post, 2 ins. in dia., 10 ins. above ground, with brass cap marked, and witnessed as described in the field notes of T. 28 S., R. 3 E. N.0*02'W., bet. secs. 34 and 35. Desc. 190 ft. over NE. slope, through open heavy timber.
11.50	Draw, drains NE., ascend 480 ft. over SE. slope to $\frac{1}{4}$ sec. cor.
12.80	Trail, bears SE. and W.
22.00	Leave timber, bears E. and W., thence over open grass land.