

## County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

79.88

The cor. of secs. 26, 27, 34 and 35.

Land, mountainous.

Soil, gravelly and rocky, 2nd rate.

Timber, fir, pine, hemlock and cedar.

Undergrowth, huckleberry, small fir, pine and hemlock.

14.88

N.0°02'W., bet. secs. 26 and 27.

Descend 440 ft. over NE. slope to  $\frac{1}{4}$  sec. cor., through heavy timber and medium undergrowth.

Creek, 2 lks. wide, course NE.

40.00

Set an iron post, 3 ft. long, 1 in. in dia., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked.
$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 27 \quad | \quad \text{S } 26 \\ | \\ 1929 \end{array}$$

from which,

A pine, 10 ins. in dia., bears N.22°E., 39 lks. dist., marked  $\frac{1}{4}$  S 26 B TA fir, 17 ins. in dia., bears N.83°W., 32 lks. dist., marked  $\frac{1}{4}$  S 27 B T

Descend 850 ft. over N. slope to sec. cor., enter dense, undergrowth.

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap marked.

$$\begin{array}{c} \text{T } 27 \text{ S } R \text{ } 3 \text{ E} \\ \hline \text{S } 22 \quad | \quad \text{S } 23 \\ \hline \text{S } 27 \quad | \quad \text{S } 26 \\ 1929 \end{array}$$

from which,

A fir, 20 ins. in dia., bears N.26°E., 31 lks. dist., marked T 27 S R 3 E S 23 B T

A fir, 20 ins. in dia., bears S.52°E., 34 lks. dist., marked T 27 S R 3 E S 26 B T

A fir, 20 ins. in dia., bears S.32°W., 18 lks. dist.,