

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.  
Subdivision.

CHAINS

with brass cap marked.

T 27 S R 3 E  
S 15 | S 14  
S 22 | S 23  
1929

from which,

A fir, 20 ins. in dia., bears N.51\*E., 24 lks. dist.,  
marked T 27 S R 3 E S 14 B T

A pine, 8 ins. in dia., bears S.29\*E., 23 lks. dist.,  
marked T 27 S R 3 E S 23 B T

A pine, 24 ins. in dia., bears S.7\*W., 76 lks. dist.,  
marked T 27 S R 3 E S 22 B T

A pine, 24 ins. in dia., bears N.56\*W., 64 lks. dist.,  
marked T 27 S R 3 E S 15 B T

Land, mountainous.

Soil, sandy and gravelly, 2nd rate.

Timber, fir, pine and hemlock.

Undergrowth, rhododendron, hazel, willow and vine  
maple.

40.00

N.89\*48'E., on a rndom line, bet. secs. 14 and 23.

Set temp. 1/4 sec. cor.

79.80

Intersect N. and S. line, 28 lks. N. of the cor. of  
secs. 13, 14, 23 and 24.

Thence,

West, on a true line.

Ascend 50 ft. over SE. slope, through heavy timber and  
dense undergrowth.

9.50

Spur, bears S., descend 125 ft. over SW. slope.

20.25

Foot of descent on S. slope, ascend 60 ft. over SE. slope.

29.50

Spur, bears S. descend 160 ft. over SW. slope to

39.90

Set an iron post, 3 ft. long, 1 in. in dia., 30 ins. in  
the ground, for 1/4 sec. cor., with brass cap marked.