

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

A pine, 8 ins. in dia., bears N.61°E., 14 lks. dist.,
marked $\frac{1}{4}$ S 11 B T

A pine, 8 ins. in dia., bears N.27 $\frac{1}{2}$ °W., 37 lks. dist.,
marked $\frac{1}{4}$ S 10 B T

65.37 Creek, $\frac{3}{4}$ lks. wide, course SW.

80.00 Set an iron post, 3 ft. long, 2 ins. dia., 32 ins. in
the ground, for cor. of secs. 2, 3, 10 and 11, with
brass cap marked.

T	27	S	R	3	E
	S	3	S	2	
	S	10	S	11	
					1929

from which,

A pine, 16 ins. in dia., bears N.45 $\frac{1}{2}$ °E., 61 lks. dist.,
marked T 27 S R 3 E S 2 B T

A pine, 20 ins. in dia., bears S.33°E., 32 lks. dist.,
marked T 27 S R 3 E S 11 B T

A pine, 14 ins. in dia., bears S.63°W., 87 lks. dist.,
marked T 27 S R 3 E S 10 B T

A pine, 12 ins. in dia., bears N.18°W., 80 lks. dist.,
marked T 27 S R 3 E S 3 B T

Land, rolling.

Soil, sandy and gravelly, 1st and 2nd rate.

Timber, fir, pine and hemlock.

Undergrowth, mountain laurel, thorn, hazel, service,
willow, small fir, pine and hemlock.

N.89°54'E., on a random line, bet. secs. 2 and 11.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.10 Intersect N. and S. line, 9 lks. S. of the cor. of
secs. 1, 2, 11 and 12.

Thence,

S.89°50'W., on a true line.

Over nearly level land, through scattering stunted