

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 26 ins. in the ground, for cor. of secs. 27, 28, 33 and 34, with brass cap marked.

T 27	S	R 3	E
S 28	S	S 27	
S 33	S	S 34	
1929			

from which,

A fir, 32 ins. in dia., bears N.39*E., 56 lks. dist., marked T 27 S R 3 E S 27 B T

A fir, 20 ins. in dia., bears S.18*E., 61 lks. dist., marked T 27 S R 3 E S 34 B T

A fir, 34 ins. in dia., bears S.12*W., 40 lks. dist., marked. T 27 S R 3 E S 33 B T

A fir, 14 ins. in dia., bears N.19*W., 51 lks. dist., marked T 27 S R 3 E S 28 B T

Land, mountainous.

Soil, sandy, gravelly, and rocky, 2nd and 3rd rate.

Timber, fir, pine, and hemlock.

Undergrowth, huckleberry, vine maple, rhododendron, small fir, and pine.

East, on a random line, bet. secs. 27 and 34.

40.00

Set temp. $\frac{1}{4}$ sec. cor.

80.36

Intersect N. and S. line, 16 lks. S. of the cor. of secs. 26, 27, 34 and 35.

Thence,

S.89*53'W., on a true line.

Ascend 480 ft. over NE. slope, through heavy timber and medium undergrowth.

22.50

Spur, bears N., descend 740 ft. over W. slope to

40.18

Set a country rock, 32x16x12 ins., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N. face; from which,