

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

15.90 Creek, 2 lks. wide, course NE., thence over N. slope.

18.17 Creek, 2 lks. wide, course NE., ascend 45 ft. over NE. slope.

20.50 Spur, bears N., descend 180 ft. over broken NW. slope to

39.96 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.
$$\begin{array}{r} \frac{1}{4} S 22 \\ \frac{1}{4} S 27 \\ 1929 \end{array}$$

from which,

A fir, 26 ins. in dia., bears N.35*E., 21 lks. dist., marked $\frac{1}{4}$ S 22 B TA fir, 20 ins. in dia., bears S.30*W., 61 lks. dist., marked $\frac{1}{4}$ S 27 B T

Descend 370 ft. over NW. slope.

63.30 Creek, 10 lks. wide, course NE., ascend 65 ft. over NE. slope.

67.50 Spur, bears N. descend 25 ft. over NW. slope.

69.80 Creek, 2 lks. wide, course NE., ascend 100 ft. over E. slope to

79.92 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous.

Soil, sandy and gravelly, 2nd and 3rd rate.

Timber, fir, pine and hemlock.

Undergrowth, rhododendron, vine maple, hazel, small fir, pine and yew.

N.0*02*W., bet. secs. 21 and 22.

Ascend 95 ft. over SE. slope, through heavy timber and dense undergrowth.

10.00 Spur, bears NE., descend 100 ft. over broken NW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.