

## County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

from which,

A fir, 8 ins. in dia., bears N.71°E., 15 lks. dist.,  
marked T 27 S R 3 E S 21 B T

A fir, 30 ins. in dia., bears S.43°E., 5 lks. dist.,  
marked T 27 S R 3 E S 28 B T

A fir, 8 ins. in dia., bears S.17°W., 8 lks. dist.,  
marked T 27 S R 3 E S 29 B T

A fir, 22 ins. in dia., bears N.24½°W., 43 lks. dist.,  
marked T 27 S R 3 E S 20 B T

Land, mountainous.

Soil, gravelly and rocky, 2nd and 3rd rate.

Timber, fir, pine, hemlock and cedar.

Undergrowth, rhododendron, vine maple, hazel, small  
fir, pine, and hemlock.

N.89°58'E., on a random line, bet. secs. 21 and 28.

40.00 Set temp. ¼ sec. cor.

80.34 Intersect N. and S. line, 23 lks. S. of the cor. of  
secs. 21, 22, 27 and 28.

Thence,

S.89°48'W., on a true line.

Ascend 350 ft. over SE. slope, through medium timber  
and dense undergrowth.

34.50 Spur, bears NE., descend 120 ft. over NW. slope.

40.17 Cut a cross ( X ) on surface rock, 2x2 ft., facing  
W., for ¼ sec. cor., cut ¼ W. of the cross, and  
build a mound of stone, 3 ft. base, 1½ ft. high, 2 ft.  
W. of the cross; from which,

A fir, 24 ins. in dia., bears S.75½°W., 68 lks. dist.,  
marked ¼ S 28 B T

A fir, 24 ins. in dia., bears N.61°W., 54 lks. dist.,  
marked ¼ S 21 B T