

Township 27 South, Range 3 East.

Subdivision.

CHAINS

From the standard cor. of secs. 31 and 32, T. 27 S., R. 3 E., which is an iron post, 2 ins. in dia., 18 ins. above ground, firmly set in a mound of stone, with brass cap marked and witnessed as described in the field notes of T. 28 S., R. 3 E.

N.0*04'W., bet. secs. 31 and 32.


Ascend 45 ft. over S. slope, through heavy timber and light undergrowth.

15.00 Spur, bears SW., descend 300 ft. over NW. slope, enter dense undergrowth.

35.80 Creek, 4 lks. wide, course SW.

36.80 Draw, drains, SW., ascend 35 ft. over SE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.



from which,

A fir, 14 ins. in dia., bears N.22*E., 11 lks. dist., marked $\frac{1}{4}$ S 32 B T


A pine, 28 ins. in dia., bears N.37*W., 23 lks. dist., marked $\frac{1}{4}$ S 31 B T

Ascend 255 ft. over SE. slope.

73.50 Spur, bears SW., descend 25 ft. over NW. slope.

76.25 Draw, drains SW., ascend 25 ft. over SW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 30 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap marked.



from which,

A fir, 6 ins. in dia., bears N.31*E., 49 lks. dist., marked T 27 S R 3 E S 29 B T