

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS	
	<p>A fir, 20 ins. in dia., bears N.32$\frac{1}{2}$*W., 78 lks. dist., marked $\frac{1}{4}$ S 30 B T</p> <p>Ascend 20 ft. over SW. slope.</p>
43.25	Spur, bears SW., descend 320 ft. over SE. slope.
63.60	Creek, 1 lk. wide, course SE., ascend 45 ft. over SW. slope.
71.20	Spur, bears S., descend 15 ft. over SE. slope.
72.60	Creek, 1 lk. wide, course SW., ascend 35 ft. over SW. slope to
80.18	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, mountainous.</p> <p>Soil, sandy, gravelly, and rocky, 2nd and 3rd rate.</p> <p>Timber, fir, pine, hemlock, and cedar.</p> <p>Undergrowth, vine maple, rhododendron, huckleberry, hazel, small fir, pine, and hemlock.</p>
	<p>N.0*04*W., bet. secs. 29 and 30.</p> <p>Ascend 590 ft. over SW. slope, through scattering timber and dense undergrowth.</p>
17.60	Trail, bears NW. and SE.
33.50	Ridge, bears E. and W., descend 85 ft. over NW. slope to
40.00	<p>Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, to bed rock, and build a mound of stone, 3 ft. base, 1$\frac{1}{2}$ ft. high, around the post, for $\frac{1}{4}$ sec. cor., with brass cap marked.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 30 \text{ } \text{S } 29 \\ \\ 1929 \end{array}$ </div> <p>from which,</p> <p>A fir, 32 ins. in dia., bears S.7*E., 34 lks. dist., marked $\frac{1}{4}$ S 29 B T</p> <p>A fir, 15 ins. in dia., bears S.81*W., 35 lks. dist.,</p>