

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS

and medium undergrowth.

27.25 Spur, bears NW., descend 250 ft. over NE. slope to
 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 19 \mid \text{S } 20 \\ | \\ 1929 \end{array}$$

from which,

A fir, 10 ins. in dia., bears S.37*E., 53 lks. dist.,
 marked $\frac{1}{4}$ S 20 B T

A fir, 14 ins. in dia., bears N.47*W., 17 lks. dist.,
 marked $\frac{1}{4}$ S 19 B T

Descend 280 ft. over NE. slope.

49.60 Dry bed of creek, 5 lks. wide, course NW. ascend 310 ft.
 over broken SW. slope.

66.60 Spur, bears NW., descend 340 ft. over NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in
 the ground, for cor. of secs. 17, 18, 19, and 20,
 with brass cap marked.

$$\begin{array}{c} \text{T } 27 \text{ S } \text{R } 3 \text{ E} \\ \text{S } 18 \mid \text{S } 17 \\ \text{S } 19 \mid \text{S } 20 \\ 1930 \end{array}$$

from which,

A fir, 12 ins. in dia., bears N.66*E., 30 lks. dist.,
 marked T 27 S R 3 E S 17 B T

A fir, 9 ins. in dia., bears S.39*E., 41 lks. dist.,
 marked T 27 S R 3 E S 20 B T

A fir, 9 ins. in dia., bears S.28 $\frac{1}{2}$ *W., 27 lks. dist.,
 marked T 27 S R 3 E S 19 B T

A fir, 10 ins. in dia., bears N.1*W., 55 lks. dist.,
 marked T 27 S R 3 E S 18 B T

Land, mountainous.

Soil, gravelly and rocky, 3rd rate.

Timber, fir, pine, hemlock, and cedar.