

County Surveyor's Record, Douglas County, Oregon

10127
87

Township 27 South, Range 3 East.

Subdivision.

CHAINS	
	$\frac{1}{4} \frac{S 8}{S 17}$ 1930
	from which, A pine, 10 ins. in dia., bears N.19*E., 20 lks. dist., marked $\frac{1}{4}$ S 8 B T A pine, 10 ins. in dia., bears S.69*W., 23 lks. dist., marked $\frac{1}{4}$ S 17 B T Ascend 210 ft. over NE. slope.
59.40	Trail and ridge, bears NW. and SE., descend 310 ft. over NW. slope to
80.06	The cor. of secs. 7, 8, 17, and 18, Land, mountainous. Soil, sandy, gravelly, and rocky, 2nd to 4th rate. Timber, fir, pine, and hemlock. Undergrowth, rhododendron, chinquapin, small fir, pine, and hemlock.
40.00	N.89*39*W., on a random line, bet. secs. 7 and 18. Set temp. $\frac{1}{4}$ sec. cor.
79.81	Intersect W. bdy. of Tp. 2 lks. N. of the cor. of secs. 7, 12, 13, and 18. Thence, S.89*40*E., on a true line. Ascend 150 ft. over W. slope, through medium timber and dense undergrowth.
6.90	Spur, bears NW. and a trail, bears NW. and SE., descend 575 ft. over NE. slope.
31.40	Creek, 6 lks. course NW., ascend 350 ft. over SW. slope to
39.81	Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.
	$\frac{1}{4} \frac{S 7}{S 18}$ 1930