

County Surveyor's Record, Douglas County, Oregon

Township 27 South, Range 3 East.

Subdivision.

CHAINS	
	and medium undergrowth.
27.00	Spur, bears NE., desc. 155 ft. over NW. slope to
39.95	Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, to bed rock, and build a mound of stone, 3 ft. base, 1½ ft. high, around the post, for ¼ sec. cor., with brass cap marked.
	$\begin{array}{r} S\ 5 \\ \hline \frac{1}{4} \\ S\ 8 \\ 1930 \end{array}$
	from which,
	A fir, 20 ins. in dia., bears S.60°E., 70 lks. dist., marked ¼ S 8 B T
	A fir, 14 ins. in dia., bears N.10°E., 44 lks. dist., marked ¼ S 5 B T
	Descend 35 ft. over NW. slope.
41.65	Creek, 1 lk. wide, course NW., thence over N. slope.
45.00	Draw, drains N., ascend 35 ft. over NE. slope.
51.00	Rock spur, bears N., descend 110 ft. over NW. slope.
58.00	Draw, drains N., ascend 270 ft. over NE. slope.
77.75	Spur, bears N., descend 15 ft. over W. slope to
79.90	The cor. of secs. 5, 6, 7, and 8.
	Land, mountainous.
	Soil, sandy, gravelly, and rocky, 2nd and 3rd rate.
	Timber, fir, pine, hemlock, and cedar.
	Undergrowth, rhododendron, chinquapin, vine maple, small fir, pine, and hemlock.
	N.89°40'W., on a random line, bet. secs. 6 and 7.
40.00	Set temp. ¼ sec. cor.
79.79	Intersect W. bdy. of Tp., 2 lks. N. of the cor. of secs. 1, 6, 7, and 12.
	Thence,
	S.89°41'E., on a true line.