

North Boundary of T. 27 S., R. 6 E.,
 as surveyed by Samuel C. Flint, U. S. Deputy Surveyor
 under contract No. 484, dated July 28, 1883.

P. 7-10185
 are duplicate of
 P. 5-10185-10185

CHAINS

From the corner to Ts. 26 & 27 S., Rs. 5 & 6 E., I run East, on random line between said townships. I set Temp. half-mile and mile cors. at each 40 and 80 chs. and find the Tp. line to be 6 miles, 36 lks., and the falling to be 42 lks. N. of the cor. to Tps. 26 and 27 S., Rs. 6 and $6\frac{1}{2}$ E. The correction for the true line will therefore be 7 lks. south and 36 lks. East per mile, and its course N. $89^{\circ}57'W$.

From the cor. to Tps. 26 & 27 S., Rs. 6 & $6\frac{1}{2}$ E., which is a post, 4 ins. sqr., firmly set in the ground, and marked T 26 S S 31 on NE, R $6\frac{1}{2}$ E S 6 on SE, T 27 S S 1 on SW, and R 6 E S 36 on NW, faces, with 6 notches on N, S, E, and W, edges. Thence I run N. $89^{\circ}57'W$. on true line bet. secs. 1 and 36
 Var. $18^{\circ}30'E$.

Descending

38.00 Dry ravine course NW.

40.00 Set post, 44x4x4 ins. sqr. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face, from which
 A Pine, 8 ins. diam., bears N. $2^{\circ}E$., 13 lks. dist. marked $\frac{1}{4}$ S B T.
 A Pine, 8 ins. diam., bears S. $40^{\circ}W$., 32 lks. dist., marked $\frac{1}{4}$ S B T.

49.25 Bottom of dry ravine, course NW.,

67.30 Bottom of dry ravine, course NW.,

80.00 Set post, 48x4x4 ins. sqr., 20 ins. in the ground, for cor. to secs. 36, 1, 2, & 35, marked T 26 S S 36 on NE, R 6 E S 1 on SE., T 27 SS 2 on SW, and S 35 on NW, faces, with 1 notch on E. and 5 on W. edges, from which
 A Pine, 8 ins. diam., bears N. $20^{\circ}E$., 4 lks. dist., marked T 26 S R 6 E S 36 B T.