

County Surveyor's Record, Douglas County, Oregon

4

26

North Bdry. of T. 27 S., R. 7 E.

CHAINS

N.89*57'W., on true line bet. secs. 4 and 33.

Var. 19*30'E.

Descend hill.

- 40.00 Set post, 44x4x4 ins. sqr. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face from which
- A Pine, 10 ins. diam., bears S.65*W., 7 lks. dist., marked $\frac{1}{4}$ S B T.
- A Pine, 7 ins. diam., bears N.1*E., 8 lks. dist., marked $\frac{1}{4}$ S B T.

Descending.

- 80.00 Set post, 48x4x4 ins. sqr. 20 ins. in the ground, for cor. to secs. 33, 4, 5, & 32, marked T 26 S S 33 on NE, R 6 E S 4 on SE, T 27 SS 5 on SW, and S. 32 on NW, faces, with 4 notches on E, and 2 on W, edges, from which
- A Pine, 6 ins. diam., bears N.25*E., 16 lks, dist., marked T 26 S R 6 E S 33 B T.
- A Pine, 7 ins. diam., bears S.45*E., 27 lks. dist., marked T 27 S R 6 E S 4 B T.
- A Pine, 6 ins. diam., bears S.65*W., 18 lks. dist., marked T 27 S R 6 E S 5 B T.
- A Pine, 6 ins. diam., bears N.55*W., 8 lks. dist., marked T 26 S R 6 E S 32 B T.

Land, hilly and rough, Densely covered with forests of pine and fir timber.

Thick underbrush of cinnamon pine and fir.

Soil, fourth rate.

Aug. 21, 1883.

N.89*57'W. on true line bet. secs. 5 and 32.

Var. 19*E.

Descending.

- 35.00 Bottom of hill.
- 36.00 Ascend hill.