

County Surveyor's Record, Douglas County, Oregon

West Boundary of T. 27 S., R. 6 E.

CHAINS	
	<p>A pine, 24 ins. diam., bears S.80*E., 74 lks. dist. Marked T 27 S R 6 E S 30 M C B T.</p> <p>A pine, 24 ins. diam., bears N.42*W., 98 lks. dist. Marked T 27 S R 5 E S 25 M C B T.</p>
33.00	<p>Thence I run North on true line between secs. 25 and 30, and at</p> <p>Set post, 44x4x4 ins. sqr., 15 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face, from which</p> <p>A pine, 12 ins. diam., bears N.62*E., 19 lks. dist. Marked $\frac{1}{4}$ S B T.</p> <p>A pine, 14 ins. diam., bears S.60*W., 20 lks. dist. Marked $\frac{1}{4}$ S B T.</p>
80.00	<p>Through burnt and fallen timber 20 chs:</p> <p>Set post, 50x4x4 ins. sqr., 22 ins., in the ground for cor. to secs. 19, 30, 25 and 24, marked T 27 S 19 on NE, R 6 E S 30 on SE, R 5 E S 25 on SW and S 24 on NW faces, with 2 notches on S and 4 on N edges, from which</p> <p>A pine, 18 ins. diam., bears N.75*E., 163 lks. dist. Marked T 27 S R 6 E S 19 B T.</p> <p>A pine, 8 ins. diam., bears S.24*E., 83 lks. dist. Marked T 27 S R 6 E S 30 B T.</p> <p>A pine, 8 ins. diam., bears S.48*W., 196 lks. dist. Marked T 27 S R 5 E S 25 B T.</p> <p>A pine, 36 ins. diam., bears N.17*W., 132 lks. dist. Marked T 27 S R 5 E S 24 B T.</p> <p>Land, hilly and rough. Thick underbrush of pine, fir and manzanita. Timber, pine and fir, soil, fourth rate.</p> <p style="text-align: right;">Aug. 18th., 1883.</p>
40.00	<p>North, on true line between secs. 24 and 19. Var. 18*10'E.</p> <p>Set post, 44x4x4 ins. sqr., 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face, from which</p>