

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 27 S., R. 6 E.

CHAINS

A fir, 36 ins. diam., bears N.23\*E., 179 lks. dist.

Marked T 27 S R 6 E S 36 B T.

A hemlock, 24 ins. diam., bears N.50\*W., 66 lks. dist.

Marked T 27 S R 6 E S 35 B T.

A pine, 16 ins. diam., bears S.15\*E., 40 lks. dist.

Marked S B T.

Var. 20\*E.

Along West slope of hill.

40.00 Set a post 44x4 ins. sqr., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face, from which

A fir, 24 ins. diam., bears N.85\*E., 31 lks. dist.

Marked  $\frac{1}{4}$  S B T.

A fir, 24 ins. diam., bears S.20\*W., 15 lks. dist.

Marked  $\frac{1}{4}$  S B T.

80.00 Set post 48x4 ins. sqr., 24 ins. in the ground for cor. to secs. 25, 36, 35 and 26, marked T 27 S S 25 on NE., R 6 E S 36 on SE., S 35 on SW. and S 26 on NW. faces with 1 notch on S. and E. edges, from which

A fir, 30 ins. diam., bears N.65\*E., 9 lks. dist.

Marked T 27 S R 6 E S 25 B T.

A fir, 36 ins. diam., bears S.40\*E., 13 lks. dist.

Marked T 27 S R 6 E S 36 B T.

A fir, 36 ins. diam., bears S.23\*W., 23 lks. dist.

Marked T 27 S R 6 E S 35 B T.

A fir, 20 ins. diam., bears N.42\*W., 47 lks. dist.

Marked T 27 S R 6 E S 26 B T.

Land, high and mountainous, covered with dense forests of pine, fir, and hemlock timber.

Thick underbrush of same kind of woods.

Soil, 3rd rate.

September 7th 1883.

East, on random line, bet. secs. 25 and 36.

Var. 19\*30'E.