

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S., R. 6 E.

## CHAINS

North, on line between secs. 32 and 33.

Var. 20\*E.

From the stand. cor. between secs. 32 and 33 which is a post 4 ins. sqr., firmly set in ground, marked S. C T. 27 S R 6 E on N., S 33 on E., and S 32 on W. faces with 4 notches on the E. and 2 on W. edges, from which

A pine, 16 ins. diam., bears N.25\*E., 62 lks. dist.

Marked T 27 S R 6 E S 33 B T.

A pine, 10 ins. diam., bears N.50\*W., 38 lks. dist.

Marked T 27 S R 6 E S 32 B T.

A pine, 12 ins. diam., bears S.75\*W., 17 lks. dist.

Marked S B T.

Thence I run as follows

32.20 Stream, 3 lks. wide, course W.

40.00 Set post 44x4 ins. sqr., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S on W. face, from which

A fir, 7 ins. diam., bears S.30\*E., 29 lks. dist.

Marked  $\frac{1}{4}$  S B T.

A fir, 5 ins. diam., bears S.5\*W., 11 lks. dist.

Marked  $\frac{1}{4}$  S B T.

54.50 Summit of hill. E. and W.

Descending.

80.00 Set post 50x4 ins. sqr., 18 ins. in the ground for cor. to secs. 28, 33, 32 and 29, marked T 27 S S 28 on NE., R 6 E S 33 on SE., S 32 on SW., and S 29 on NW. faces with 1 notch on the S. and 4 on the E. edges, from which

A pine, 6 ins. diam., bears N.40\*E., 26 lks. dist.

Marked T 27 S R 6 E S 28 B T.

A pine, 10 ins. diam., bears S.35\*E., 66 lks. dist.

Marked T 27 S R 6 E S 33 B T.

A pine, 8 ins. diam., bears S.10\*W., 17 lks. dist.

Marked T 27 S R 6 E S 32 B T.