

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S., R. 6 E.

CHAINS	
40.00	Set post 44x4 ins. sqr., 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face, from which A pine, 10 ins. diam., bears S.85*W., 25 lks. dist. Marked $\frac{1}{4}$ S B T. A fir, 10 ins. diam., bears S.55*E., 38 lks. dist. Marked $\frac{1}{4}$ S B T.
44.90	Stream, 3 lks. wide, course W.
80.00	Set post 50x4 ins. sqr., 20 ins. in the ground for cor. to secs. 21, 28, 29 and 20, marked T 27 S S 21 on NE., R 6 E S 28 on SE., S 29 on SW., and S 20 on NW. faces with 2 notches on S. and 4 on E. edges, from which A pine, 14 ins. diam., bears N.25*E., 21 lks. dist. Marked T 27 S R 6 E S 21 B T. A pine, 10 ins. diam., bears S.55*E., 23 lks. dist. Marked T 27 S R 6 E S 28 B T. A pine, 8 ins. diam., bears S.50*W., 14 lks. dist. Marked T 27 S R 6 E S 29 B T. A pine, 8 ins. diam., bears N.65*W., 16 lks. dist. Marked T 27 S R 6 E S 20 B T. Land, mountainous and rough. Timber, pine and fir, scattering. Thick pine and fir underbrush. Soil, 2nd. rate.
	East, on random between secs. 21 and 28. Var. 19*30'E.
40.00	Set temp. $\frac{1}{4}$ sec. cor. and at
79.90	Intersect N. and S. line 10 lks. South of cor. to secs. 21, 22, 27 and 28. Thence I run S.89*56'W. with same var. on true line bet. secs. 21 and 28. Descending.
39.95	Set post 44x4 ins. sqr., 15 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face, from which A pine, 8 ins. diam., bears S.40*W., 9 lks. dist.