

County Surveyor's Record, Douglas County, Oregon

10169

Subdivisions of T. 27 S., R. 6 E.

| CHAINS | |
|--------|--|
| | <p>Marked $\frac{1}{4}$ S B T.</p> <p>A pine, 12 ins. diam., bears N.5*W., 30 lks. dist.</p> <p>Marked $\frac{1}{4}$ S B T.</p> |
| 49.90 | Stream, 6 lks. wide, course N. |
| 79.90 | The corner to secs. 20, 21, 28 and 29. |
| | <p>Land, rough and mountainous, covered with forests of pine and fir timber. Thickly covered with pine and fir brush. Soil, 3rd. rate.</p> |
| | <p>West, on true line bet. secs. 29 and 32.</p> <p style="text-align: right;">Var. 20*E.</p> |
| 20.00 | Summit of hill. |
| 20.50 | Descend hill. |
| 40.00 | <p>Set post 44x4 ins. sqr., 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face, from which</p> <p>A pine, 6 ins. diam., bears S.23*E., 15 lks. dist.</p> <p>Marked $\frac{1}{4}$ S B T.</p> <p>A pine, 7 ins. diam., bears S.20*W., 14 lks. dist.</p> <p>Marked $\frac{1}{4}$ S B T.</p> |
| 79.00 | Bottom of hill. |
| 80.00 | <p>Set post 50x4 ins. sqr., 20 ins. in the ground for cor. to secs. 29, 32, 31 and 30, marked T 27 S S 29 on NE., R 6 E S 32 on SE., S 31 on SW, and S 30 on NW. faces with 1 notch on S. and 5 on E. edges, from which</p> <p>A fir, 6 ins. diam., bears N.25*E., 25 lks. dist.</p> <p>Marked T 27 S R 6 E S 29 B T.</p> <p>A fir, 8 ins. diam., bears S.45*E., 32 lks. dist.</p> <p>Marked T 27 S R 6 E S 32 B T.</p> <p>A pine, 20 ins. diam., bears S.14*W., 25 lks. dist.</p> <p>Marked T 27 S R 6 E S 31 B T.</p> <p>A fir, 8 ins. diam., bears N.12*W., 41 lks. dist.</p> <p>Marked T 27 S R 6 E S 30 B T.</p> <p>Land, hilly, covered with pine, fir and hemlock timber, heavy and good. Underbrush thick of pine and fir.</p> <p>Soil, 3rd. rate.</p> |

September 12th 1883.