

North Boundary of T. 27 S., R. 6 $\frac{1}{2}$  E.,  
 as surveyed by Samuel C. Flint, Deputy Surveyor,  
 under contract No. 484, dated July 28, 1883.

CHAINS

From the cor. to Tps. 26 & 27 S., Rs. 6 & 6 $\frac{1}{2}$  E., I run East on random line bet. said Tps. and set a temp.  $\frac{1}{4}$  sec. post in sec. 5 at 51.60: from there, on East set temp. half-mile and mile post at 40 and 80 chains, and find the Tp. line to be 5 miles, 11 chains, 80 lks. long, and the falling to be 15 lks. S. of cor. to Tps. 26 & 27 S., of Rs. 6 $\frac{1}{2}$  & 7 E. The correction of the true line will be 2 $\frac{1}{2}$  lks. S. per mile, and its course S.89\*59'W. Thence I run

S.89\*59'W., on north bdy. of sec. 1.

Va. 18\*E.

Ascending.

40.00 Set post, 44x4x4 ins. sqr. 14 ins. in the ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on N. face from which

A fir, 12 ins. in diam., bears N.10\*W., 28 lks. dist. marked  $\frac{1}{4}$  S B T.

A fir, 12 ins. in diam., bears S.25\*E., 31 lks. dist. marked  $\frac{1}{4}$  S B T.

Still ascending.

70.30 Enter small prairie.

78.00 Leave prairie and enter timber.

80.00 Set post, 48x4x4 ins. sqr. 22 ins. in the ground, for cor. to secs. 1, 2, 35, & 36, marked T 27 S R 6 $\frac{1}{2}$  E S 1 on SE., S 2 on SW., T 26 on S R 6 $\frac{1}{2}$  E S 36 on NE., and S. 35 on NW., faces, with 1 notch on E. and 5 on W. edges, from which

A fir, 12 ins. in diam., bears N.50\*E., 26 lks. dist. marked T 26 S R 6 $\frac{1}{2}$  E S 36 B T.

A fir, 20 ins. in diam., bears S.70\*E., 12 lks. dist. marked T 27 S R 6 $\frac{1}{2}$  E S 1 B T.

A fir, 12 ins. in diam., bears S.12\*W., 51 lks. dist. marked T 27 S R 6 $\frac{1}{2}$  E S 2 B.T.