

County Surveyor's Record, Douglas County, Oregon

N. Bdy. of T. 27 S., R. 6 $\frac{1}{2}$ E.

CHAINS

A fir, 18 ins. in dia., bears N.55*W., 24 lks. dist.,
marked T 26 S R 6 $\frac{1}{2}$ E S 35 B T.

Land, rough and mountainous.

Densely covered with forests of pine and fir timber.

Soil, 3rd rate.

S.89*59*W., on true line on N. boundary of sec. 2.

Va. 18*E.

19.00 Summit of mountain, Course N.30*W.

27.00 Descend mountain.

40.00 Set post, 44x4x4 ins. sqr. 15 ins. in the ground, for $\frac{1}{4}$
sec. cor. marked $\frac{1}{4}$ S., on N. face, from which

A fir, 30 ins. in diam., bears S.55*W., 30 lks. dist.
marked $\frac{1}{4}$ S B T.

A fir, 16 ins. in diam., bears N.15*E., 59 lks. dist.
marked $\frac{1}{4}$ S B T.

Descending.

80.00 Set post, 48x4x4 ins. sqr. 20 ins. in the ground for cor.
to secs. 2, 3, 34, and 35 marked T 26 S R 6 $\frac{1}{2}$ E S 35 on
NE. T 27 S R 6 $\frac{1}{2}$ E S 3 on SW., T 27 S R 6 $\frac{1}{2}$ E S 2 on SE.,
T 26 S S 34 on NW., faces with 2 notches on E. and 4
notches on W. edges, from which

A fir, 24 ins. in diam., bears N.51*E., 28 lks. dist.,
marked T 26 S R 6 $\frac{1}{2}$ E S 35 B T.

A fir, 20 ins. in diam., bears S.25*E., 16 lks. dist.,
marked T 27 S R 6 $\frac{1}{2}$ E S 2 B T.

A fir, 8 ins. in diam., bears S.52*W., 40 lks. dist.
marked T 27 S R 6 $\frac{1}{2}$ E S 3 B T.

A fir, 24 ins. in diam., bears N.20*W., 28 lks. dist.
marked T 26 S R 6 $\frac{1}{2}$ E S 34 B T.

This mile is rough and mountainous.

Densely covered with forests of fir and pine timber.

Soil, 3rd rate.
