

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 27 S. R. 6 $\frac{1}{2}$ E.

CHAINS	
	North between Sec. 23 and 24. Va. 17*30'E.
2.75	Stream, 3 lks. wide, course NE.
11.50	Bottom of dry ravine.
40.00	Set post, 44 ins. by 4 ins. sq. 12 ins. in the ground, on E. slope of hill for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face, from which: A pine, 16 ins. diam., bears S.80*E., 10 lks. dist., marked $\frac{1}{4}$ S B T A pine, 24 ins. diam., bears S.45*W., 37 lks. dist., marked $\frac{1}{4}$ S B T
68.50	Bottom of dry ravine.
80.00	Set pine post, 50 ins. by 4 ins. sq. 18 ins. in the ground, for cor. to secs. 13, 14, 23 and 24, marked T 27 S S 13 on NE.- R 6 $\frac{1}{2}$ E S 24 on SE- S 23 on SW. and Sec. 14 NW. faces, with 3 notches on S. and 1 on the E. edges, from which: A pine, 16 ins. diam., bears N.40*E., 51 lks. dist., marked T 27 S R 6 $\frac{1}{2}$ E S 13 B T A pine, 12 ins. diam., bears S.75*E., 17 lks. dist., marked T 27 S R 6 $\frac{1}{2}$ E S 24 B T A pine, 8 ins. diam., bears S.30*W., 26 lks. dist., marked T 27 S R 6 $\frac{1}{2}$ E S 23 B T A pine, 8 ins. diam., bears N.30*W., 13 lks. dist., marked T 27 S R 6 $\frac{1}{2}$ E S 14 B T
	Land steep and hilly.
	Soil 3rd. rate.
	Dense forests of pine and fir timber.
	Some undergrowth of pine and fir.
	East on random bet. secs. 13 and 24. Va. 17*30'E.
40.00	Set temp. $\frac{1}{4}$ sec. cor. and at
79.90	Intersect E. bdy. of T. 25 lks. S. of cor. to secs. 13 and 24, which is a post 4 ins. sq., marked T 27 S R 6 $\frac{1}{2}$ E S 24 on SW. Sec. 13 on NW. and R 7 E S 19 on NE. faces, and with 3 notches on N. and S. edges, from which: