

## County Surveyor's Record, Douglas County, Oregon

43

Subdivisions of T. 27 S. R. 6 $\frac{1}{2}$  E.

CHAINS	Secs. 17 and 20. Ascending ridge.
17.75	Summit of main ridge, course N. and S.
52.25	Set post, 44 ins. by 4 ins. sq. 12 ins. in the ground, for $\frac{1}{4}$ S cor., marked $\frac{1}{4}$ S on N. face, from which: A fir, 18 ins. diam., bears N.20*E., 11 lks. dist., marked $\frac{1}{4}$ S B T A fir, 20 ins. diam., bears S.15*W., 9 lks. dist., marked $\frac{1}{4}$ S B T
92.25	Cor. to secs. 16, 17, 20 and 21. Land high, rocky and mountainous, covered in part with dense forests and in part, scattering fir and pine timber. Thick underbrush of pine and fir. Soil 4th rate.  Sept. 3rd. 1883.
	North, bet. secs. 13 and 14. Va. 17*30'E.
7.50	Summit of ridge, bears E. and W.
8.00	Descend towards lake.
40.00	Set post, 44 ins. by 4 ins. sq. 12 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face, from which: A pine, 12 ins. diam., bears N.89*E., 15 lks. dist., marked $\frac{1}{4}$ S B T A pine, 10 ins. diam., bears S.55*W., 32 lks. dist., marked $\frac{1}{4}$ S B T
49.75	Stream, 4 lks. wide, course NE.
56.00	Intersect Fish Lake. Set meander post, 48 by 4 ins. sq. 15 ins. in the ground, bet. fracl. secs. 13 and 14., marked M C T 27 S R 6 $\frac{1}{2}$ E S 13 on E. S 14 on W. faces, and MC on N. face, from which: A fir, 10 ins. diam., bears S.55*E., 5 lks. dist., marked T 27 S R 6 $\frac{1}{2}$ E S 13 M C B T