

Sixth Standard Parallel South, through R. 5 E.,
As surveyed by, Samuel C. Flint, U. S. Deputy Surveyor,
Under contract No. 473, dated June 5, 1883.

CHAINS	
	Va. 17*30'E.
	East, on S. bdy. of sec. 31.
	Ascend hill.
40.00	Set post, 45x4 ins. firmly in the ground, for stan. $\frac{1}{4}$ sec. cor. mkd. S C on N. and S. faces, from which
	A pine, 16 ins. diam., bears S.27*W., 188 lks. dist., mkd. S C 1/4 S B T.
	A pine, 16 ins. diam., bears N.33*E., 148 lks. dist., mkd. S C 1/4 S B T.
	Desc. mountain.
75.81	Stream, 20 lks. wide, course N.
80.00	Set post, 48x4 ins. firmly in the ground, for stan. cor. to secs. 31 and 32, mkd. S C T 27 S R 5 E on N, S 32 on E, and S 31 on W, faces, with 5 notches on E. and 1 on W. edges, from which
	A fir, 10 ins. diam., bears N.48*E., 13 lks. dist., mkd. T 27 S R 5 E S 32 B T.
	A fir, 12 ins. diam., bears N.28*W., 24 lks. dist., mkd. T 27 S R 5 E S 31 B T.
	A fir, 30 ins. diam., bears S.32*W., 12 lks. dist., mkd. S B T.
	Land, 4th rate, mountainous and rough.
	Timber, fir, hemlock, spruce and pine.
	Underbrush, thick of fir and hemlock.
	Va. 21*E.
	East, on S. bdy. of sec. 32.
	Up a very steep ridge.
40.00	Set post, 44x4 ins. firmly in the ground, for stan. 1/4 sec. cor. mkd. S C on N. and S. faces, from which
	A fir, 8 ins. diam., bears N.55*W., 8 lks. dist., mkd. S C 1/4 S B T.
	A fir, 8 ins. diam., bears S.42*W., 22 lks. dist., mkd. S C 1/4 S B T.