

Sixth Standard Parallel South, through R. 4 E.,

CHAINS

A fir, 20 ins. diam., bears N.45*W., 16 lks. dist.,
mkd. S C 1/4 S B T.

54.95 Stream, 8 lks. wide, course N.

78.00 Leave branch and ascend high ridge.

80.00 Set post, 50x4 ins. firmly in the ground, for stan. cor.
to secs. 32 and 33, mkd. S C T 27 S R 4 E on N, Sec. 33
on E, and S 32 on W. faces, with 4 notches on E, and
2 on W. edges, from which

A fir, 30 ins. diam., bears N.20*E., 8 lks. dist.,
mkd. T 27 S R 4 E S 33 B T.

A fir, 30 ins. diam., bears N.74*W., 32 lks. dist.,
mkd. T 27 S R 4 E S 32 B T.

A fir, 36 ins. diam., bears S.42*W., 20 lks. dist.,
mkd. S B T.

Land, 2nd rate.

Timber, good fir, hemlock and pine.

Underbrush, thick of vine maple, laurel and fir.

Mountainous.

July 6, 1883.

Va.18*E.

East, on S. bdy. of sec. 33.

Ascend steep ridge.

40.00 Set post, 44x4 ins. firmly in the ground, for stan. 1/4
sec. cor. mkd. S C on N. and S. faces, from which

A fir, 14 ins. diam., bears N.22*E., 17 lks. dist.,
mkd. S C 1/4 S B T.

A fir, 16 ins. diam., bears S.15*E., 7 lks. dist.,
mkd. S C 1/4 S B T.

The above 1/4 post is estimated to be about 1,000 ft.
above last sec. cor.

77.00 Summit of ridge, N. and S. estimated 5,000 ft. high.